


TECHNICAL DATA SHEET

PAVING, PORCELAIN & STONE

JOINT RESIDUE REMOVER



Softens hard to remove epoxy, acrylic and silicone residues left by cement free brush in jointing compounds making removal easier.

A low odour non caustic treatment that softens hard to remove epoxy, acrylic and silicone residues left by cement free brush in jointing compounds making removal from the surface of natural stone and porcelain paving much easier.

DIRECTIONS FOR USE

SHAKE WELL BEFORE USE.

Always test on an inconspicuous area prior to general use.

Preparation: Ensure that the surface to be treated is completely clean and dry. If necessary, first wash surfaces with ECOPROTEC Intensive Cleaner. Rinse well with water to finish and leave to dry.

Removing Residues: Apply generously by dabbing or rolling onto the surface. Work in manageable areas at a time and do not brush out. Leave for up to 30 minutes. If drying should occur within 30 minutes apply a little more solution to keep it wet. Use a stiff short haired brush or nylon scrubbing pad to remove the softened residues from the surface. Add a little water and scrub again. Extract the released residues using a sponge or wet vac and rinse with water. Repeat the process if unwanted material remains.

To finish: Use ECOPROTEC Intensive cleaner dilute 1: 5 in warm water. Apply with a light pressure sprayer or watering can. Agitate the surface using a deck brush or nylon scrubbing pad. Rinse by hosing off thoroughly with clean water.

Do not use when surface temperatures are under 5°C or over 25°C.

Light Stripping	8-10m ²
Deep Stripping	5m ²

STORAGE INFORMATION

Store in a cool, dry, frost-free environment. Shelf life up to 2 years for un-opened containers. Once opened use within 6 months of purchase for optimum results.

OTHER

Do not apply during rain, frost, or when surface and air temp is under 5°C or over 30°C. Use gloves and protective goggles if there is a risk of direct contact or splashing. Empty containers are recyclable. Clean application tools and brushes with water after use. Once cleaned: Protect porous stone and porcelain with ECOPROTEC Ultimate Sealer or Patio Sealer or Colour Enhancing Sealer.

HEALTH, SAFETY & ENVIRONMENTAL

CONTAINS: benzyl alcohol.

Harmful if swallowed or if inhaled. Causes serious eye irritation.

Keep out of reach of children. IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do not breathe vapours, spray. Wash hands thoroughly after handling. Do not eat, drink, or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents, container to a hazardous or special waste collection point.



WARNING



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.